



# M10

The M10 is a high-performance dual 10" monitor loudspeaker engineered for professional audio environments. Delivering exceptional sound clarity across a 60 Hz to 20 kHz frequency range, this monitor provides expansive 50° horizontal and 100° vertical coverage with remarkable precision.

Designed with professional flexibility in mind, the M10 features compact dimensions of 20.5" width, 12.75" height, and 21.25" depth, weighing 22 kg. The monitor includes an integrated pole mount and a kickstand allowing up to 45° face tilt, accommodating diverse acoustic settings.

A powered version (MG10) is also available. The M10 represents a perfect blend of acoustic excellence, robust engineering, and versatile performance, making it an ideal solution for studio, live sound, and installation applications that demand superior audio quality.

## Specifications

Frequency Range (+/- 3dB)	60 Hz - 20 kHz
Nominal Directivity (-6 dB) H x V	50° x 100°
Maximum Peak SPL **	139 dB
Components LF	2x ND10-LM 10" Kevlar Neodymium Driver
Components HF	Adamson NH3 3" Diaphragm / 1.4" Exit Compression Driver
Nominal Impedance LF	8Ω
Nominal Impedance HF	8Ω
Power Handling (AES / Peak) LF	700 / 2800 W
Power Handling (AES / Peak) HF	120 / 480 W
Rigging	Integrated Pole Mount
Connection	2x Speakon NL4
Height (mm / in)	324 / 12.75
Width (mm / in)	520 / 20.5
Depth (mm / in)	540 / 21.25
Weight (kg / lbs)	22 / 48.51
Processing	Lake

\*\*12 dB crest factor pink noise at 1m, free field, using specified processing and amplification

