



MG10

The MG10 is a high-performance dual 10" monitor loudspeaker engineered for professional audio environments. Delivering exceptional sound clarity across a 60 Hz to 20 kHz frequency range, this monitor provides expansive 50° horizontal and 100° vertical coverage with remarkable precision.

Its integrated 2-channel Class-D amplifier produces an impressive maximum SPL of 139 dB, ensuring powerful and dynamic sound reproduction. Designed with professional flexibility in mind, the MG10 features compact dimensions of 20.5" width, 12.75" height, and 21.25" depth, weighing 26 kg. The monitor includes an integrated pole mount and a kickstand allowing up to 45° face tilt, accommodating diverse acoustic settings.

A passive version (M10) is also available. The MG10 represents a perfect blend of acoustic excellence, robust engineering, and versatile performance, making it an ideal solution for studio, live sound, and installation applications that demand superior audio quality.

Specifications

| | |
|-----------------------------------|---|
| Frequency Range (+/- 3dB) | 60 Hz - 20 kHz |
| Nominal Directivity (-6 dB) H x V | 50° x 100° |
| Maximum Peak SPL ** | 139 dB |
| Components LF | 2x ND10-LM 10" Kevlar Neodymium Driver |
| Components HF | Adamson NH3 3" Diaphragm / 1.4" Exit Compression Driver |
| Rigging | Integrated Pole Mount |
| Connection | Power: powerCON TRUE1 Network: 2x etherCON Analog: 2x XLR |
| Height (mm / in) | 324 / 12.75 |
| Width (mm / in) | 520 / 20.5 |
| Depth (mm / in) | 540 / 21.25 |
| Weight (kg / lbs) | 26 / 57.3 |
| Amplification | 2 channel Class-D, 2400 W total output |
| Input Voltage | 100 - 240 V |
| Current Draw | 230 V 0.45 A rms idle, 1.6 A rms long-term, 10 A maxpeak |
| Processing | Onboard / Proprietary |

**12 dB crest factor pink noise at 1m, free field, using specified processing and amplification

